

Multi Touch Screen

A Series (2, 6, 32 points and more)

True Multi Touch and **Excellent Slim Design**
with **Infrared Touch Screen**



Features

- True Multi Touch without Ghost
- Slim Bezel
- High Speed & Reliability
- Working under Sunlight
- Easy Installation
- Integrated Controller

Applications

- Digital Signage
- Kiosk
- ATM
- Medical Instrument
- Commercial Transportation
- Industrial Applications



Multi Touch Screen

A Series (2, 6, 32 points and more)

Specifications

Touch Panel

Technology	Infrared Touch
Available Sizes	10.4 inch ~ 103 inch (Custom sizes available upon request)
Touch Input Method	Pen, finger, gloved hand or any other pointer
Minimum Touch Object	5~7mm (depends on each model and size)
Touch Activation Force	No minimum touch activation force is required
Touch Response Time	4.5 ~15 ms (depends on each model and size)
Resolution	16384 x 16384 (based on controller resolution)
Touch Durability	Unlimited
Housing	Aluminum, Black
Glass	Option (Custom versions available upon request)

Electrical

Operating Voltage	DC4.6V ~ 5.25V
Power Supply	USB Powered (for screen size < 60 inch) Adapter Powered (for screen size ≥ 60 inch)
Power	USB : ≤ 2W Adapter : ≤ 3.5W
Interface	USB2.0 Full speed, HID Compliant Plug & Play
Operating Systems	Windows XP, Vista, Windows 7, Windows 8, Linux, Mac, Android

Environmental

Temperature	Operating : -10℃ ~ +60℃ Storage : -40℃ ~ +85℃ (8hr still)
Humidity	Operating : 10% ~ 90% RH(Non-condensing) Storage : 10% ~ 95% RH(Non-condensing)

* The specification is subject to change without prior notice

